

dishwash dosing systems

BrightLogic D2

For tunnel or conveyor dishwashers, choose the new BrightLogic D2 – part of the new BrightLogic series of highly durable, easy-to-use dispensers.

Like the D1, the D2 can automatically dose two products, only the D2 can do it simultaneously.

New brushless motors ensure the pumps have a very long life.

The versatility of this dispenser means it can work in timed/signal mode, with conductive and inductive probes, or by using the cyclic mode.

The front-facing splash guard has ample space for brand promotion – or promote your brand on the unit's electronic screen. The simple user interface is available in many languages and can be security-code programmed to ensure smooth, uninterrupted operations.

Other features include, diagnostic on-screen testing and the ability to disable the prime, pump-stop and view modes, for increased security



The D2 can be ordered with high-flow pumps – giving a flow rate of up to 1000ml per minute.

This makes it ideal for crate washers in hygienic food-production environments.

When ordering ensure you refer to an IP-LOGIC-D2



IP-Logic-D2



illuminated screen

| | |
|-------------------|--|
| power | 90 V-265V AC, 50-60Hz, current @90V - 0.33A, @265V-0.11A |
| flowrate | 6.4mm Silicone - 350ml/min (flowrate taken using water at 100% speed) |
| control circuitry | microprocessor controller with 16x2 illuminated alphanumeric LCD display programming via 5 external keypad keys, security access code |
| motor | brushless - 24V DC, 600mA |
| enclosure | glass filled polypropylene enclosure and plaque |
| options | inductive or conductive probe |
| installation kit | available on request |
| approvals | EMC 89/336/EEC - EN61000-6-2:2005 EN61000-6-3:2007 LVD 72/23/EEC - EN60335-1:2002+A2:2006 |
| dimensions (mm) | H266 x W285 x D132 logo (max) - H40 x W40 |
| weight (approx.) | 2.1kg |
| order reference | D2 |

Flowrates using other tubing are available on request

